

## C-201A-16-ND Product Specifications



### COMBO A With No Back D-Ring:

- 3 Pt adjustment
- Light weight harness
- Heavy duty leg/chest straps
- 5,000 Lbs rated heavy duty nylon webbing
- Lanyard Latch ring
- Size : M - XL (Universal) Also available in oversized and extra padding
- Plated hardware for corrosion resistance
- Forged hardware parts
- 1 Adjustable back D-ring for fall protection and restraint purpose
- Insertion buckle at chest and legs
- Attached 6' lanyard with internal shock pack

DESCRIPTION	RATED TENSILE STRENGTH
1 ¾" TAN AND ORANGE NYLON WEBBING	7,000 LBS
1 ¾" PLATED INSERTION STYLE BUCKLE	4,000 LBS
Lanyard 1 ¾" Tubular Nylon/Polyester webbing	5,000 LBS
PLASTIC LANYARD/ELASTIC KEEPER	N/A
Meets or exceeds applicable OSHA and ANSI standards, including ANSI Z359.1	

#### Testing References:

Webbing: ANSI Z359 3.2.2.2 – 3.2.2.7

D-rings: ANSI Z359 3.2.1.5 and 3.2.1.7

Buckles: ANSI Z359 3.2.1.6

Harness: ANSI Z359 3.2.2.7

Testing Procedure: ANSI Z359 4.3.3.1 and 4.3.3.2

Performance Rating: 5,000lbs Static Load

OSHA requires that the employer shall provide a training program for each employee who might be exposed to fall hazards. As part of the training program, the user of this product must:

- Become familiar with all instructions contained in the product manual
- Be trained in the correct use and care of their equipment
- Be aware of its application limitations
- Know and understand the consequences of improper use
- FAILURE TO FOLLOW INSTRUCTIONS MAY RESULT IN SERIOUS INJURY OR DEATH

